

WHAT IS CLAIMED IS:

Sub
A3

1. A basket assembly for a dishwashing machine comprising:
a basket defining at least one compartment; and
a handle attached to said basket, said handle selectively positionable
between a first position and a second position, one of said first and second positions
allowing substantially unobstructed access to said compartment.

2. A basket assembly in accordance with Claim 1 wherein said basket
comprises at least one handle bracket, said handle attached to said bracket, said
bracket configured for maintaining said handle in said first position and said second
position.

3. A basket assembly in accordance with Claim 2 wherein said basket
comprises a longitudinal axis, said handle extending substantially parallel to said
longitudinal axis.

4. A basket assembly in accordance with Claim 2 wherein said handle
is contoured to form finger grips therein.

5. A basket assembly in accordance with Claim 2 wherein said bracket
comprises a crown, said handle comprising a peg for insertion into said crown, one of
said peg and said crown including a first detent and a second detent therein, the other
of said peg and said crown comprising a projection for engagement with said first
detent and said second detent.

6. A basket assembly in accordance with Claim 5 wherein said handle
includes a gripper portion and an attachment portion extending therefrom, said peg
extending from said attachment portion.

7. A basket assembly in accordance with Claim 5 wherein said crown
is substantially round.

8. A basket assembly in accordance with Claim 5 wherein said detent
is substantially round.

9. A basket assembly in accordance with Claim 5 wherein said handle
is channel-shaped in cross section.

10. A basket assembly for a dishwashing machine comprising:

Sub
P4
a substantially rectangular basket comprising first and second lateral side walls having a first length and first and second longitudinal side walls having a second length, said second length greater than said first length,

5 a handle attached to said lateral side walls and comprising a contoured gripper portion therebetween, said handle selectively positionable between a first position and a second position, one of said first and second positions allowing substantially unobstructed access to said compartment.

10 11. A basket assembly in accordance with Claim 5 wherein said gripper portion is U-shaped in cross section.

12. A basket assembly in accordance with Claim 10 wherein said basket further comprises a handle bracket attached to each of said lateral side walls, said handle attached to said bracket, said bracket configured for maintaining said handle in said first position and said second position.

15 13. A basket assembly in accordance with Claim 11 wherein said handle comprises opposite attachment portions extending from said gripper portion, each of said attachment portions comprising a peg configured to be received by said handle brackets.

20 14. A basket assembly in accordance with Claim 13 wherein each of said brackets comprises a crown, one of said pegs and said crowns including a first detent and a second detent therein, the other of said pegs and said crowns comprising a projection for engagement with said first detent and said second detent.

15. A basket assembly in accordance with Claim 14 wherein said crown is substantially round.

25 16. A basket assembly in accordance with Claim 14 wherein said detent is substantially round.

Add
A5